

VERTICAL HOLLOSHAFT® HIGH THRUST MOTORS – “P” BASE SINGLE PHASE, WEATHER PROTECTED TYPE I (WPI) STANDARD EFFICIENT

VHS
WPI
STD EFF
1 PHASE

APPLICATIONS:

For use on Turbine, Mix Flow and Propeller Pumps

FEATURES:

- Equipped with Non-Reverse Ratchet
- 1.15 Service Factor, 40°C Ambient
- Class F Insulation
- Capacitor Start Design
- Corrosion Resistant Mill & Chemical Duty Paint

HP	RPM	FRAME	VOLTS	CATALOG NUMBER	TYPE	LIST \$ W/NRR	LIST \$ W/SRC	DOWN THRUST (LBS.)	BASE DIA. (IN.)	CPLG HEIGHT (IN.)	CPLG BX (IN.)	CPLG KEY SIZE	SHIP WT. (LBS.)	NOTES
3	3600	213P	115/230	HS3C1PLE	AUR	\$1,884	\$1,780	2200	10	17-9/16	1	1/4	210	
	1800	215P	115/230	HS3C2PLE	AUR	\$1,946	\$1,828	2500	10	17-9/16	1	1/4	220	
5	3600	215P	230	HS5C1KLE	AUR	\$2,036	\$1,918	2200	10	17-9/16	1	1/4	220	
	1800	254UP	230	HS5C2KLE	AUC	\$2,466	\$2,326	2500	10	23-3/8	1	1/4	265	
7-1/2	3600	254UP	230	HS7C1KLE	AUC	\$2,904	\$2,764	2600	10	23-3/8	1	1/4	265	
	1800	256UP	230	HS7C2KLE	AUC	\$3,336	\$3,176	3300	10	23-3/8	1	1/4	300	

NOTE: Alternative Coupling Sizes per Frame Size are listed beginning on Page 32.

Most stock VHS Motors include a Non-Reverse Ratchet (NRR), as indicated by their Catalog Number. To order a Motor with a Self-Release Coupling (SRC), add an "N" as the last character in the Catalog Number. Example: HO50S2BLG includes NRR; HO50S2BLGN is SRC.

Discount Symbol: DS-7VS

VERTICAL HOLLOSHAFT® HIGH THRUST MOTORS – “P” BASE THREE PHASE, WEATHER PROTECTED TYPE I (WPI) STANDARD EFFICIENT

VHS
WPI
STD EFF
3 PHASE 60 Hz

APPLICATIONS:

For use on Turbine, Mix Flow and Propeller Pumps

FEATURES:

- Class F Insulation, Class B Rise at Full Load (Sine Wave Power)
- 1.15 Service Factor (Sine Wave Power)
- Maximum 40°C Ambient, 3,300 Feet Altitude
- 230/460 Volt Motors Suitable for 230 Volt Part Winding Start
- 30 HP & Below Can Be Re-rated For 208/415 Volt
50 Hertz Operation at 1.0 Service Factor
- Suitable For Operation on VFD Per NEMA MG-1 Part 30 at 1.0 Service Factor
- 115 Volt Space Heater Through 250 HP
- Corrosion Resistant Mill & Chemical Duty Paint
- Stainless Steel Nameplate
- NRR = Non-Reverse Ratchet, SRC = Self-Release Coupling

HP	RPM	FRAME	VOLTS	CATALOG NUMBER	TYPE	LIST \$ W/NRR	LIST \$ W/SRC	% FL EFF.	DOWN THRUST (LBS.)	BASE DIA. (IN.)	CPLG HEIGHT (IN.)	CPLG BX (IN.)	CPLG KEY SIZE	SHIP WT. (LBS.)	NOTES
7-1/2	1200	254TPH	230/460	HO7S3BLF	AU	\$1,558	\$1,398	86.5	3800	12	23-3/8	1	1/4	265	
10	1200	256TPH	230/460	HO10S3BLF	AU	\$1,762	\$1,598	87.5	3800	12	23-3/8	1	1/4	300	
15	1800	254TP	230/460	HO15S2BLE	AU	\$1,536	\$1,396	89.5	3300	10	23-3/8	1	1/4	265	
	1800	254TPA	230/460	HO15S2BLG	AU	\$1,536	\$1,396	89.5	3300	16-1/2	23-3/8	1	1/4	265	
	1200	284TPA	230/460	HO15S3BLF	AU	\$2,054	\$1,879	88.5	3800	12	24-3/4	1	1/4	305	
20	3600	254TPH	230/460	HO20S1BLF	AU	\$1,632	\$1,482	88.5	2600	12	23-3/8	1	1/4	265	
	1800	256TPA	230/460	HO20S2BLG	AU	\$1,750	\$1,590	89.5	3300	16-1/2	23-3/8	1	1/4	300	
	1800	256TPH	230/460	HO20S2BLF	AU	\$1,750	\$1,590	89.5	3300	12	23-3/8	1	1/4	300	
	1200	286TPH	230/460	HO20S3BLG	AU	\$2,470	\$2,270	88.5	3800	16-1/2	24-3/4	1	1/4	325	
25	3600	256TPH	230/460	HO25S1BLF	AU	\$1,726	\$1,562	89.5	2600	12	23-3/8	1	1/4	300	
	1800	284TPA	230/460	HO25S2BLF	AU	\$1,952	\$1,774	88.5	3300	12	24-3/4	1	1/4	305	
	1800	284TPH	230/460	HO25S2BLG	AU	\$1,952	\$1,774	88.5	3300	16-1/2	24-3/4	1	1/4	305	
	1200	324TP	230/460	HO25S3BLG	RU	\$2,850	\$2,620	87.5	6700	16-1/2	28-7/32	1	1/4	635	
30	3600	284TPA	230/460	HO30S1BLF	AU	\$1,890	\$1,718	88.5	2600	12	24-3/4	1	1/4	305	
	1800	286TPA	230/460	HO30S2BLF	AU	\$2,194	\$1,996	90.2	3300	12	24-3/4	1	1/4	325	
	1800	286TPH	230/460	HO30S2BLG	AU	\$2,194	\$1,996	90.2	3300	16-1/2	24-3/4	1	1/4	325	
	1200	326TP	230/460	HO30S3BLG	RU	\$3,254	\$2,990	87.5	6700	16-1/2	28-7/32	1-1/4	3/8	675	
40	3600	286TPA	230/460	HO40S1BLF	AU	\$2,470	\$2,246	90.2	2600	12	24-3/4	1	1/4	325	
	1800	324TP	230/460	HO40S2BLG	RU	\$2,550	\$2,344	89.5	5700	16-1/2	28-7/32	1-1/4	1/4	635	
	1800	324TP	230/460	HO40S2BLGN	RU	N/A	\$2,344	89.5	5700	16-1/2	28-7/32	1-1/4	1/4	635	91
	1800	324TP	460	HO40S2SLG	RU	\$2,550	\$2,344	89.5	5700	16-1/2	28-7/32	1-1/4	1/4	635	PWS
	1800	324TPH	230/460	HO40S2BLF	RU	\$2,550	\$2,344	89.5	5700	12	28-7/32	1-1/4	1/4	635	
	1200	364TP	230/460	HO40S3BLGX	RU	\$3,976	\$3,654	88.5	11725	16-1/2	31-5/32	1-1/4	3/8	730	
50	3600	324TPH	230/460	HO50S1BLF	RU	\$2,806	\$2,578	88.5	4600	12	28-7/32	1	1/4	635	
	1800	326TP	230/460	HO50S2BLG	RU	\$3,026	\$2,780	90.2	5700	16-1/2	28-7/32	1-1/4	1/4	675	
	1800	326TP	230/460	HO50S2BLGN	RU	N/A	\$2,780	90.2	5700	16-1/2	28-7/32	1-1/4	1/4	675	91
	1800	326TP	460	HO50S2SLG	RU	\$3,026	\$2,780	90.2	5700	16-1/2	28-7/32	1-1/4	1/4	675	PWS
	1800	326TPH	230/460	HO50S2BLF	RU	\$3,026	\$2,780	90.2	5700	12	28-7/32	1-1/4	1/4	675	
	1200	365TP	230/460	HO50S3BLGX	RU	\$4,688	\$4,308	90.2	11725	16-1/2	31-5/32	1-1/4	3/8	800	
60	3600	326TP	460	HO60S1SLG	RU	\$3,348	\$3,076	89.5	4600	16-1/2	28-7/32	1-1/4	1/4	675	PWS
	1800	364TP	230/460	HO60S2BLG	RU	\$3,494	\$3,212	90.2	5700	16-1/2	31-5/32	1-1/4	1/4	730	
	1800	364TP	230/460	HO60S2BLGN	RU	N/A	\$3,212	90.2	5700	16-1/2	31-5/32	1-1/4	1/4	730	91
	1800	364TP	460	HO60S2SLG	RU	\$3,494	\$3,212	90.2	5700	16-1/2	31-5/32	1-1/4	1/4	730	PWS
	1200	404TP	460	HO60S3SLGX	RU	\$5,354	\$4,920	89.5	13650	16-1/2	36-15/16	1-1/2	3/8	1110	PWS

Discount Symbol: DS-7VS

VERTICAL HOLLOSHAFT® HIGH THRUST MOTORS – “P” BASE THREE PHASE, WEATHER PROTECTED TYPE I (WPI) STANDARD EFFICIENT

VHS
WPI
STD EFF
3 PHASE 60 Hz

APPLICATIONS:

For use on Turbine, Mix Flow and Propeller Pumps

HP	RPM	FRAME	VOLTS	CATALOG NUMBER	TYPE	LIST \$ W/NRR	LIST \$ W/SRC	% FL EFF.	DOWN THRUST (LBS.)	BASE DIA. (IN.)	CPLG HEIGHT (IN.)	CPLG BX (IN.)	CPLG KEY SIZE	SHIP WT. (LBS.)	NOTES
75	3600	364TP	460	HO75S1SLG	RU	\$4,188	\$3,850	89.5	4500	16-1/2	31-5/32	1-1/4	1/4	730	PWS
	1800	365TP	230/460	HO75S2BLG	RU	\$4,254	\$3,910	91.7	5700	16-1/2	31-5/32	1-1/4	1/4	800	
	1800	365TP	230/460	HO75S2BLGN	RU	N/A	\$3,910	91.7	5700	16-1/2	31-5/32	1-1/4	1/4	800	91
	1800	365TP	460	HO75S2SLG	RU	\$4,254	\$3,910	91.7	5700	16-1/2	31-5/32	1-1/4	1/4	800	PWS
	1200	405TP	460	HO75S3SLGX	RU	\$6,296	\$5,786	89.5	13650	16-1/2	36-15/16	1-1/2	3/8	1200	PWS
100	3600	365TP	460	HO100S1SLG	RU	\$5,644	\$5,186	91.0	4500	16-1/2	31-5/32	1-1/4	3/8	800	PWS
	1800	404TP	230/460	HO100S2BLG	RU	\$5,374	\$4,940	93.0	6700	16-1/2	36-15/16	1-1/2	3/8	1110	
	1800	404TP	460	HO100S2SLG	RU	\$5,374	\$4,940	93.0	6700	16-1/2	36-15/16	1-1/2	3/8	1110	PWS
	1800	404TP	460	HO100S2SLGX	RU	\$5,602	\$5,168	93.0	11725	16-1/2	36-15/16	1-1/2	3/8	1110	PWS
125	1800	405TP	460	HO125S2SLG	RU	\$6,492	\$5,966	93.0	6700	16-1/2	36-15/16	1-1/2	3/8	1200	PWS
	1800	405TP	460	HO125S2SLGX	RU	\$6,768	\$6,242	93.0	11725	16-1/2	36-15/16	1-1/2	3/8	1200	PWS
150	1800	H444TP	460	HO150S2SLG	RU	\$7,810	\$7,256	92.4	9800	16-1/2	44-25/32	1-11/16	3/8	1500	PWS
	1800	H444TP	460	HO150S2SLGX	RU	\$8,150	\$7,596	92.4	17150	16-1/2	44-25/32	1-11/16	3/8	1500	PWS
	1800	H444TPA	460	HO150S2SLH	RU	\$7,810	\$7,256	92.4	9800	20	44-25/32	1-11/16	3/8	1500	PWS
200	1800	H445TP	460	HO200S2SLG	RU	\$10,612	\$9,858	93.6	9800	16-1/2	44-25/32	1-11/16	3/8	1600	PWS
	1800	H445TPA	460	HO200S2SLHX	RU	\$11,072	\$10,318	93.6	17150	20	44-25/32	1-11/16	3/8	1600	PWS
250	1800	H445TPA	460	HO250S2SLHX	RU	\$12,756	\$12,188	93.0	17150	20	44-25/32	1-11/16	3/8	1600	PWS
300	1800	447TPA	460	HO300S2SLHX	RU	\$15,049	\$14,518	94.5	17150	20	49-25/32	1-11/16	3/8	2200	51, PWS
350	1800	447TPA	460	HO350S2SLHX	RU	\$17,379	\$16,848	94.5	17150	20	49-25/32	1-11/16	3/8	2200	51, PWS
400	1800	447TPA	460	HO400S2SLHX	RU	\$19,707	\$19,176	95.0	29400	20	49-25/32	1-15/16	1/2	2200	51,52,53, PWS
500	1800	5008PH	460	HO500S2SLHX	RU	\$24,017	\$23,417	95.4	29400	20	57-1/16	2-3/16	1/2	3125	52,53, PWS
600	1800	5008P	460	HO600S2SLJX	RU	\$36,095	\$35,495	95.0	30500	24-1/2	57-1/16	2-3/16	1/2	3700	52,53, PWS

NOTE: Alternative Coupling Sizes per Frame Size are listed beginning on Page 32

Most stock VHS Motors include a Non-Reverse Ratchet (NRR), as indicated by their Catalog Number. To order a Motor with a Self-Release Coupling (SRC), add an "N" as the last character in the Catalog Number. Example: HO50S2BLG includes NRR, HO50S2BLGN is SRC.

Note 51: Equipped with Winding Thermostat

Note 52: Requires Minimum External Down Thrust of 3800 lbs.

Note 53: Synthetic Oil Required

Note 91: Includes Self Release Coupling (SRC)

Note PWS: Part Winding Start

Discount Symbol: DS-7VS

VERTICAL HOLLOSHAFT® HIGH THRUST MOTORS – “P” BASE THREE PHASE, WEATHER PROTECTED TYPE I (WPI) ENERGY EFFICIENT

VHS
WPI
ENE EFF
3 PHASE 60 Hz

APPLICATIONS:

For use on Turbine, Mix Flow and Propeller Pumps

FEATURES:

- Class F Insulation, Class B Rise at Full Load (Sine Wave Power)
- 1.15 Service Factor (Sine Wave Power)
- Maximum 40°C Ambient, 3,300 Feet Altitude
- 230/460 Volt Motors Suitable for 230 Volt Part Winding Start
- 30 HP & Below Can Be Re-rated For 208/415 Volt
50 Hertz Operation at 1.0 Service Factor
- Suitable For Operation on VFD Per NEMA MG-1 Part 30 at 1.0 Service Factor
- 115 Volt Space Heater
- Corrosion Resistant Mill & Chemical Duty Paint
- Stainless Steel Nameplate
- NRR = Non-Reverse Ratchet, SRC = Self-Release Coupling

HP	RPM	FRAME	VOLTS	CATALOG NUMBER	TYPE	LIST \$ W/NRR	LIST \$ W/SRC	% FL EFF.	DOWN THRUST (LBS.)	BASE DIA. (IN.)	CPLG HEIGHT (IN.)	CPLG BX (IN.)	CPLG KEY SIZE	SHIP WT. (LBS.)	NOTES
7-1/2	1800	213TP	230/460	HO7E2BLE	AUE	\$1,407	\$1,303	90.2	2500	10	17-9/16	1	1/4	210	
10	1800	215TP	230/460	HO10E2BLE	AUE	\$1,551	\$1,433	90.2	2500	10	17-9/16	1	1/4	220	
25	1800	284TPH	230/460	HO25E2BLG	AUE	\$2,388	\$2,210	92.4	3300	16-1/2	24-3/4	1	1/4	305	
30	1800	286TPH	230/460	HO30E2BLG	AUE	\$2,630	\$2,432	92.4	3300	16-1/2	24-3/4	1	1/4	325	
40	1800	324TP	230/460	HO40E2BLG	RUE	\$3,145	\$2,939	93.6	5700	16-1/2	28-7/32	1-1/4	1/4	635	
	1800	324TP	575	HO40E2GLG	RUE	\$3,145	\$2,939	93.0	5700	16-1/2	28-7/32	1-3/16	1/4	635	
	1800	324TPH	230/460	HO40E2BLF	RUE	\$3,145	\$2,939	93.6	5700	12	28-7/32	1-1/4	1/4	635	
50	1800	326TP	230/460	HO50E2BLG	RUE	\$3,621	\$3,375	93.6	5700	16-1/2	28-7/32	1-1/4	1/4	675	
	1800	326TP	575	HO50E2GLG	RUE	\$3,621	\$3,375	93.0	5700	16-1/2	28-7/32	1-3/16	1/4	675	
60	1800	364TP	460	HO60E2SLG	RUE	\$4,287	\$4,005	94.1	5700	16-1/2	31-5/32	1-1/4	1/4	730	
	1800	364TP	575	HO60E2GLG	RUE	\$4,287	\$4,005	93.6	5700	16-1/2	31-5/32	1-3/16	1/4	730	
75	1800	365TP	460	HO75E2SLG	RUE	\$5,047	\$4,703	94.1	5700	16-1/2	31-5/32	1-1/4	1/4	800	
	1800	365TP	575	HO75E2GLG	RUE	\$5,047	\$4,703	94.1	5700	16-1/2	31-5/32	1-3/16	1/4	800	
100	1800	404TP	460	HO100E2SLG	RUE	\$6,488	\$6,054	94.5	6700	16-1/2	36-15/16	1-1/2	3/8	1110	
125	1800	405TP	460	HO125E2SLG	RUE	\$7,606	\$7,080	95.0	6700	16-1/2	36-15/16	1-1/2	3/8	1200	
150	1800	H444TP	460	HO150E2SLG	RUE	\$10,205	\$9,651	95.4	9800	16-1/2	44-25/32	1-11/16	3/8	1500	
200	1800	H445TP	460	HO200E2SLG	RUE	\$13,007	\$12,253	95.4	9800	16-1/2	44-25/32	1-11/16	3/8	1600	

NOTE: Alternative Coupling Sizes per Frame Size are listed beginning on Page 32.

Most stock VHS Motors include a Non-Reverse Ratchet (NRR), as indicated by their Catalog Number. To order a Motor with a Self-Release Coupling (SRC), add an "N" as the last character in the Catalog Number. Example: HO50S2BLG includes NRR; HO50S2BLGN is SRC.

Discount Symbol: DS-7VS

VERTICAL HOLLOSHAFT® HIGH THRUST MOTORS – “P” BASE THREE PHASE, WEATHER PROTECTED TYPE I (WPI) PREMIUM EFFICIENT AND PREMIUM EFFICIENT-INVERTER DUTY

VHS
WPI
PRE EFF
VFD DUTY

APPLICATIONS:

For use on Turbine, Mix Flow and Propeller Pumps

FEATURES:

- Class F Insulation, Class B Rise at Full Load (Sine Wave Power)
- 1.15 Service Factor (Sine Wave Power)
- Maximum 40°C Ambient, 3,300 Feet Altitude
- 230/460 Volt Motors Suitable for 230 Volt Part Winding Start
- 30 HP & Below Can Be Re-rated For 208/415 Volt
50 Hertz Operation at 1.0 Service Factor
- Inverter Duty Per NEMA MG-1 Part 31 at 1.0 Service Factor
- 115 Volt Space Heater through 250 HP
- Corrosion Resistant Mill & Chemical Duty Paint
- Premium Efficient Design, Special Balance
- NRR = Non-Reverse Ratchet, SRC = Self-Release Coupling

HP	RPM	FRAME	VOLTS	CATALOG NUMBER	TYPE	LIST \$ W/NRR	LIST \$ W/SRC	% FL EFF.	DOWN THRUST (LBS.)	BASE DIA. (IN.)	CPLG HEIGHT (IN.)	CPLG BX (IN.)	CPLG KEY SIZE	SHIP WT. (LBS.)	NOTES
15	1800	254TP	230/460	HO15V2BLE	AUI	\$1,881	\$1,741	91.7	3300	10	23-3/8	1	1/4	265	97
20	1800	256TPH	230/460	HO20V2BLF	AUI	\$2,095	\$1,935	92.4	3300	12	24-3/4	1	1/4	300	97
25	1800	284TPA	230/460	HO25V2BLF	AUI	\$2,388	\$2,210	92.4	3300	12	24-3/4	1	1/4	305	97
30	1800	286TPA	230/460	HO30V2BLF	AUI	\$2,630	\$2,432	92.4	3300	12	24-3/4	1	1/4	325	97
40	1800	324TPH	230/460	HO40V2BLF	RUSI	\$3,314	\$3,108	94.1	5700	12	28-7/32	1-1/4	1/4	635	97
50	1800	326TP	230/460	HO50V2BLG	RUSI	\$3,789	\$3,543	94.5	5700	16-1/2	28-7/32	1-1/4	1/4	675	97
60	1800	364TP	460	HO60V2SLG	RUSI	\$4,485	\$4,203	94.5	5700	16-1/2	31-5/32	1-1/4	1/4	730	97
75	1800	365TP	460	HO75V2SLG	RUSI	\$5,245	\$4,901	95.0	5700	16-1/2	31-5/32	1-1/4	1/4	800	97
100	1800	404TP	460	HO100V2SLG	RUSI	\$6,767	\$6,333	95.4	6700	16-1/2	36-15/16	1-1/2	3/8	1110	97
125	1800	405TP	460	HO125V2SLG	RUSI	\$7,885	\$7,359	95.4	6700	16-1/2	36-15/16	1-1/2	3/8	1200	97
150	1800	H444TP	460	HO150V2SLG	RUSI	\$10,804	\$10,250	95.8	9800	16-1/2	44-25/32	1-11/16	3/8	1500	51,97
200	1800	H445TPA	460	HO200V2SLH	RUSI	\$13,426	\$12,672	95.8	9800	20	44-25/32	1-11/16	3/8	1600	51,97
250	1800	H445TPA	460	HO250V2SLH	RUSI	\$16,784	\$16,216	95.8	9800	20	44-25/32	1-11/16	3/8	1600	51,97
300	1800	447TPA	460	HO300V2SLH	RUSI	\$19,470	\$18,939	95.8	9800	20	49-25/32	1-11/16	3/8	2200	51,97
350	1800	447TPA	460	HO350V2SLH	RUSI	\$21,591	\$21,060	95.8	9800	20	49-25/32	1-11/16	3/8	2200	51,97
400	1800	447TPA	460	HO400V2SLH	RUSI	\$24,501	\$23,970	95.8	9800	20	49-25/32	1-15/16	1/2	2200	51,97
450	1800	5008PH	460	HO450V2SLH	RUEI	\$26,049	\$25,505	96.2	9500	20	57-1/16	1-15/16	3/8	3700	51,97

NOTE: Alternative Coupling Sizes per Frame Size are listed beginning on Page 32.

Most stock VHS Motors include a Non-Reverse Ratchet (NRR), as indicated by their Catalog Number. To order a Motor with a Self-Release Coupling (SRC), add an "N" as the last character in the Catalog Number. Example: HO50S2BLG includes NRR; HO50S2BLGN is SRC.

Note 51: Equipped With Winding Thermostat

Note 97: INVERTER GRADE® motors with inverter duty insulation

Discount Symbol: DS-7VS

VERTICAL HOLLOSHAFT® HIGH THRUST MOTORS – “P” BASE THREE PHASE, TOTALLY ENCLOSED FAN COOLED (TEFC) STANDARD EFFICIENT

VHS
TEFC
STD EFF
2 PHASE 60 HZ

APPLICATIONS:

For use on Turbine, Mix Flow and Propeller Pumps

FEATURES:

- Class F Insulation, Class B Rise at Full Load (Sine Wave Power)
- 1.15 Service Factor (Sine Wave Power)
- Maximum 40°C Ambient, 3,300 Feet Altitude
- 230/460 Volt Motors Suitable for 230 Volt Part Winding Start
- 30 HP & Below Can Be Re-rated For 208/415 Volt
50 Hertz Operation at 1.0 Service Factor
- Suitable For Operation on VFD Per NEMA MG-1 Part 30 at 1.0 Service Factor
- Corrosion Resistant Mill & Chemical Duty Paint
- Stainless Steel Nameplate
- NRR = Non-Reverse Ratchet, SRC = Self-Release Coupling

HP	RPM	FRAME	VOLTS	CATALOG NUMBER	TYPE	LIST \$ W/NRR	LIST \$ W/SRC	% FL EFF.	DOWN THRUST (LBS.)	BASE DIA. (IN.)	CPLG HEIGHT (IN.)	CPLG BX (IN.)	CPLG KEY SIZE	SHIP WT. (LBS.)	NOTES
5	3600	184TP	230/460	HT5S1BLE	TU	\$1,147	\$1,037	80.0	2200	10	17-9/16	1	1/4	170	
	1800	184TP	230/460	HT5S2BLE	TU	\$1,143	\$979	82.5	2500	10	17-9/16	1	1/4	170	
7-1/2	3600	213TP	230/460	HT7S1BLE	TU	\$1,187	\$1,071	81.5	2200	10	17-9/16	1	1/4	210	
	1800	213TP	230/460	HT7S2BLE	TU	\$1,166	\$1,020	84.0	2500	10	17-9/16	1	1/4	210	
10	3600	215TP	230/460	HT10S1BLE	TU	\$1,306	\$1,188	82.5	2200	10	17-9/16	1	1/4	220	
	1800	215TP	230/460	HT10S2BLE	TU	\$1,306	\$1,156	85.5	2500	10	17-9/16	1	1/4	220	
15	3600	215TP	230/460	HT15S1BLE	TU	\$1,546	\$1,428	86.5	2200	10	17-9/16	1	1/4	220	
	1800	254TP	230/460	HT15S2BLE	TU	\$1,995	\$1,815	88.5	3300	10	22-15/16	1	1/4	265	
20	1800	256TP	230/460	HT20S2BLE	TU	\$2,276	\$2,068	87.5	3300	10	22-15/16	1	1/4	300	
25	1800	284TPA	230/460	HT25S2BLF	TU	\$2,538	\$2,306	89.5	3300	12	26-9/16	1	1/4	320	
30	1800	286TPA	230/460	HT30S2BLF	TU	\$2,854	\$2,594	89.5	3300	12	26-9/16	1	1/4	330	
40	1800	324TP	230/460	HT40S2BLG	TU	\$3,570	\$3,280	90.2	4500	16-1/2	28-1/2	1-1/4	1/4	665	
50	1800	326TP	230/460	HT50S2BLG	TU	\$4,236	\$3,892	91.0	4500	16-1/2	28-1/2	1-1/4	1/4	690	
60	1800	364TP	460	HT60S2CLG	TU	\$5,242	\$4,816	91.7	5600	16-1/2	30	1-1/4	1/4	900	
75	1800	365TP	460	HT75S2CLG	TU	\$6,382	\$5,869	92.4	5600	16-1/2	30	1-1/4	1/4	925	
100	1800	405TP	460	HT100S2CLG	TU	\$8,600	\$7,904	93.0	7000	16-1/2	39-15/16	1-1/2	3/8	1500	
125	1800	444TP	460	HT125S2CLG	TU	\$11,190	\$10,394	92.4	9300	16-1/2	42-1/2	1-1/2	3/8	1900	

NOTE: Alternative Coupling Sizes per Frame Size are listed beginning on Page 32.

Most stock VHS Motors include a Non-Reverse Ratchet (NRR), as indicated by their Catalog Number. To order a Motor with a Self-Release Coupling (SRC), add an “N” as the last character in the Catalog Number. Example: HO50S2BLG includes NRR; HO50S2BLGN is SRC.

Discount Symbol: DS-7VS